

oventrop

„Aktor T 2P/O“
230 V

Art.-Nr.:
1012820


(NC)



Montage




Assembly
Montage




Demontage

Disassembly
Démontage






Anschluss

Connection
Raccordement



blau - blue - bleu

braun - brown - brun






First-Open

„First-Open“-Funktion
„First-Open“ function
Fonction „First-Open“

Stromlos-zu
Normally Closed

NC



≈


Power on
>6 min.

Power off



Stromlos-zu
Normally Closed

NC

Anpassungskontrolle
Adaption check
Contrôle de l'ajustement



Funktionsweise
Function mode
Mode de fonctionnement



DEU

Technische Daten

Betriebsspannung:	230 V, +10 %... - 10 %, 50/60 Hz
Betriebsleistung:	2,5 W
Einschaltstrom, max.:	300 mA für max. 200 ms
Stellkraft:	90 N ± 5 %
Stellweg:	4,0 mm
Schutzgrad:	IP 42
Umgebungstemperatur:	0 °C ... 60 °C
Lagertemperatur:	-25 °C ... 60 °C

ENG

Technical Specifications

Operating voltage:	230 V, +10 %... - 10 %, 50/60 Hz
Operating capacity:	2.5 W
Max. inrush current:	300 mA for max. 200 ms
Actuating force:	90N ± 5 %
Stroke:	4,0 mm
Type of protection:	IP 42
Ambient temperature:	0 °C ... 60 °C
Storage temperature:	-25 °C ... 60 °C

FRA

Spécifications techniques:

Tension de service:	230 V, +10 %... - 10 %, 50/60 Hz
Capacité de fonctionnement:	2,5 W
Courant de fermeture du circuit:	300 mA pendant max. 200 ms
Force:	90 N ± 5 %
Course:	4,0 mm
Type de protection:	IP 42
Température ambiante:	0 °C ... 60 °C
Température de stockage:	-25 °C ... 60 °C