

Transmission station Regudis H-MHT

For the connection of a variable temperature heating circuit (surface heating), a constant temperature heating circuit (radiators) and a potable water storage cylinder

OVENTROP transmission station Regudis H-MHT with plate heat exchanger for the indirect transmission of heat from a local or district heating network to the potable water and heating system of detached houses or multiple occupancy dwellings.

With electronic controller for the weather guided control of the flow temperature of the heating system and simultaneous limitation of the return temperature to the local/district heating network.


With pump group Regumat M3 and electric pipe contact safety switch for the connection of a variable temperature heating circuit (surface heating).

With HT switching module for the connection of a constant temperature heating circuit (radiators).

A potable water storage cylinder with internal heat exchanger can be connected to the secondary side.

For use in closed local and district heating networks, for operation with non-aggressive, harmless fluids (e.g. water or suitable water and glycol mixtures according to VDI 2035/ÖNORM 5195).

The station is supplied with mounted functional modules and is completely parameterized and tested at works.



Illust. 2: Construction of the Regudis H-MHT

- | | |
|-----|---|
| (1) | Ball valve with thermometer inside the handle |
|-----|---|




Illust. 1: Transmission station Regudis H-MHT

(2)	Connecting pipe
(3)	Safety group
(4)	Heat exchanger
(5)	Electronic controller
(6)	Pressure independent control valve Cocon QTZ with actuator
(7)	Rear insulation shell
(8)	Flanged pipe with check valve
(9)	Pump
(10)	Switching valve with 2 point actuator
(11)	Ball valve with handle (2x)
(12)	Rear insulation shell
(13)	Ball valve with thermometer inside the handle
(14)	Thermometer
(15)	Rear insulation shell
(16)	Spacer for heat meter
(17)	Strainer with venting and draining valve
(18)	Pressure gauge
(19)	Spacer for heat meter
(20)	Pressure gauge
(21)	Three-way mixing valve
(22)	Pump

Connections	
A	Primary circuit supply
B	Primary circuit return
C	Secondary circuits supply
D	Secondary circuits return


General information		
Item no.	1393037	
Designation	Regudis H-MHT	
Nominal size	DN25	
Max. operating temperatures	95°C	
Max. operating pressures	10 bar	
Min. operating pressure ps	1 bar	
Max. primary differential pressure	6 bar	
Ambient temperature T	2-35°C	
Empty weight		
Regudis H-MHT	58,44 kg	
Hydronic performance data		
Safety valve secondary side	3 bar	
Max. primary volume flow	4800 l/h	
Display range of the pressure gauge	0 - 16 bar	
Operating fluids	Water / mixtures of water and glycol	
Dimensions		
Regudis H-MHT	Width x Height x Depth (in mm)	630 x 1706 x 330
Connections to the pipework		
Transmission station	Flat sealing male thread G 1 ¼	
Ball valve connection set	Flat sealing male thread G1 ½	
Regumat	Flat sealing male thread G1 ½	
HT switching module	Flat sealing male thread G1 ½	
Electrical performance data		
Operating voltage controller	230 V AC, 50-60 Hz	
Actuator	Closed with current off, 24 V DC, control voltage 0-10 V	
Material		
Valves and fittings	Brass, bronze	

Seals	Fibre materials; EPDM
Base plate	Galvanised steel
Thermal insulation	EPP
Heat exchanger	Plate material: stainless steel 1.4401
	Connections: Stainless steel 1.4404
	Brazing material: Copper
Pipes	Stainless steel 1.4404
Spacers	Stainless steel 1.4404




Illust. 3: Dimensions in mm


Designation	Item no.
Accessories	
	Monovalent potable water storage cylinder Hydrocor WM
	1395010 1395011 1395012
Diaphragm expansion tank	1399091
	1399092
Extension module Regtronic EM	1152098
Connection set	1399080




Illust. 4: Pressure loss primary circuit Regudis H




Illust. 5: Pressure loss secondary circuit Regudis H-MHT (Regumat M 3)






Illust. 7: Performance chart; recommended max. volume flow Regudis H in combination with HT switching module



Illust. 8: Performance chart; recommended max. volume flow Regudis H in combination with Regumat S



Illust. 9: Performance chart; recommended max. volume flow Regudis H in combination with Regumat M 3