

# Regudis W-CE

## Electronic dwelling station



For the supply of individual dwellings with heating water and hot potable water. The required heat is provided by a central heat supply. Hot potable water is prepared decentrally via a plate heat exchanger according to the continuous flow principle. When selecting the dwelling station, it is necessary to consider the water quality of the area of use.

The stations consist of a plate heat exchanger, a control valve with integrated differential pressure and volume flow control, an actuator with integrated potable water temperature control, a zone valve, a volume flow sensor, a temperature sensor, a filter insert, a spacer for heat meters and, depending on the version, water meters, ceramic disc valves, angle ball valves, vent valves and drain valves.

The Regudis W-CE stations are designed for unmixed heating circuits. The stations are characterised by particularly compact dimensions and simple, fast and flexible installation. High draw-off capacities can be achieved with low excess temperatures and pressure losses.

### Features

- + Compact dimensions
- + Simple, fast and flexible installation
- + High draw-off capacity at low excess temperature
- + Optimised in terms of pressure loss

### General data

|                                    |                                                                                                                                                                                     |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Variants</b>                    | Performance range 1a-2;<br>with copper brazed heat exchanger or<br>copper brazed heat exchanger with<br>Sealix® protective layer                                                    |
| <b>Empty weight of the station</b> | 1343929: 8.7 kg<br>1343930/50: 9.6 kg<br>1343931/51: 10.4 kg<br>1343960: 8.8 kg<br>1343961: 9.4 kg                                                                                  |
| <b>Max. operating temperature</b>  | 90 °C                                                                                                                                                                               |
| <b>Max. operating pressure</b>     | 10 bar                                                                                                                                                                              |
| <b>Ambient temperature</b>         | 2...35 °C                                                                                                                                                                           |
| <b>Medium</b>                      | Heating water according to VDI 2035/Ö-Norm H 5195-1, fluid category ≤ 3 according to EN 1717. Observe the specifications of the Oventrop information sheet on corrosion protection. |

# Product Details

## Technical Data

### Dimensions and connections

|                                           |                |
|-------------------------------------------|----------------|
| <b>Width x Height x Depth</b>             | See dimensions |
| <b>Connections</b>                        | Rp ¾ IT        |
| <b>Centre distance of the connections</b> | 65 mm          |
| <b>Centre distance to wall</b>            | 26,5 mm        |

### Hydraulic data: Primary circuit (buffer storage cylinder)

|                                   |                                                                                                                                                                                     |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Medium</b>                     | Heating water according to VDI 2035/Ö-Norm H 5195-1, fluid category ≤ 3 according to EN 1717. Observe the specifications of the Oventrop information sheet on corrosion protection. |
| <b>Min. differential pressure</b> | 150 mbar                                                                                                                                                                            |
| <b>Max. differential pressure</b> | 2.0 bar                                                                                                                                                                             |
| <b>Min. flow temperature</b>      | See charts in the appendix                                                                                                                                                          |

### Hydraulic data: Heating circuit (radiators)

|                                      |                                                                                                                                                                                     |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Medium</b>                        | Heating water according to VDI 2035/Ö-Norm H 5195-1, fluid category ≤ 3 according to EN 1717. Observe the specifications of the Oventrop information sheet on corrosion protection. |
| <b>Max. volume flow</b>              | approx 460 l/h                                                                                                                                                                      |
| <b>Differential pressure control</b> | 150 mbar                                                                                                                                                                            |

### Hydraulic data: Potable water circuit

|                                   |                                                                                                      |
|-----------------------------------|------------------------------------------------------------------------------------------------------|
| <b>Medium</b>                     | Potable water. Observe the specifications of the Oventrop information sheet on corrosion protection. |
| <b>Min. cold water pressure</b>   | See charts in the appendix                                                                           |
| <b>Control range</b>              | 40...70 °C                                                                                           |
| <b>Max. hot water volume flow</b> | See charts in the appendix                                                                           |

### Electrical data: Power supply unit

|                                        |                      |
|----------------------------------------|----------------------|
| <b>Mains input voltage</b>             | 100...240 V AC ±10 % |
| <b>Mains input frequency</b>           | 50...60 Hz           |
| <b>Output voltage</b>                  | 5 V DC +7.5 %, -5 %  |
| <b>Rated output current</b>            | max. 1200 mA         |
| <b>Protection type: connection box</b> | IP66                 |
| <b>Protection class</b>                | II                   |
| <b>Overvoltage category</b>            | III                  |
| <b>Ambient temperature</b>             | 0...60 °C            |

### Electrical data: Actuator

|                            |                     |
|----------------------------|---------------------|
| <b>Input voltage</b>       | 5 V DC +7.5 %, -5 % |
| <b>Power consumption</b>   | 0.15...3 W          |
| <b>Protection type</b>     | IP54                |
| <b>Ambient temperature</b> | 0...60 °C           |

### Material

|                                                                   |                                                                                                                                           |
|-------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Heat exchanger copper brazed</b>                               | Plate material: Stainless steel 1.4401<br>Connections: Stainless steel 1.4404<br>Brazing material: Copper                                 |
| <b>Heat exchanger copper brazed with Sealix® protective layer</b> | Plate material: Stainless steel 1.4401<br>Connections: Stainless steel 1.4404<br>Brazing material: Copper<br>Protective layer: SiO2 basis |
| <b>Pipes</b>                                                      | Stainless steel 1.4404                                                                                                                    |
| <b>Valves and fittings</b>                                        | Brass                                                                                                                                     |
| <b>Temperature sensor</b>                                         | Stainless steel 1.4404                                                                                                                    |
| <b>Volume flow sensor</b>                                         | Brass and plastic                                                                                                                         |
| <b>Meter spacer</b>                                               | Plastic                                                                                                                                   |
| <b>Seals</b>                                                      | EPDM and fibre material                                                                                                                   |

# Functions

The dwelling station is an electronically controlled product assembly with heat exchanger for use in domestic areas. The product assembly provides heated potable water (hot water) within a residential unit and distributes the heating water (max. 90° C) to radiators.

The decentralised hot water preparation of the station makes the storage of hot potable water unnecessary.

In the heat exchanger, potable water is heated according to the continuous flow principle only when it is needed. The demand for hot water is detected by the volume flow sensor.

The setpoint temperature for the hot water is adjusted with the rotary knob on the actuator. During operation, the temperature sensor continuously measures the temperature of the hot water at the hot water outlet of the heat exchanger. The temperature sensor forwards this information to the electronic control.


The information from the volume flow sensor and the temperature sensor is passed on to the actuator by the electronic control.

The actuator opens and closes the control valve. Depending on the position of the control valve, more or less hot heating water flows from the primary supply into the heat exchanger as required. In addition, the control valve keeps the necessary differential pressure in the system constant.



The heat output transferred to the potable water depends on the heating water quantity and the heating water temperature supplied to the heat exchanger. The control valve features a potable water priority function ensuring the supply of the required hot water quantity even in heating mode.

Optionally, an actuator can be mounted on the zone valve. This offers you the possibility to close the zone valve time-controlled.



# Dimensions





Station including ceramic disc valves,  
cold water outlet and spacer for water meter  
Performance range 1a





Station including ceramic disc valves,  
cold water outlet and spacer for water meter  
Performance range 1



Station including ceramic disc valves,  
cold water outlet and spacer for water meter  
Performance range 2




Station including ceramic disc valves, without  
cold water outlet and spacer for water meter  
Performance range 1



Station including ceramic disc valves, without  
cold water outlet and spacer for water meter  
Performance range 2

# Connections

Station including ceramic disc valves, cold water outlet and spacer for water meter:




## Description

|   |                                                 |
|---|-------------------------------------------------|
| 1 | Primary supply from the buffer storage cylinder |
| 2 | Primary return to the buffer storage cylinder   |
| 3 | Hot water outlet                                |
| 4 | Heating circuit return                          |
| 5 | Heating circuit supply                          |
| 6 | Cold water outlet                               |
| 7 | Cold water inlet from the house connection      |

# Design

Station including ceramic disc valves, cold water outlet and spacer for water meter:



## Description


- |    |                                                                               |
|----|-------------------------------------------------------------------------------|
| 1  | Heat exchanger                                                                |
| 2  | Control valve with integrated differential pressure and volume flow control   |
| 3  | Vent valve in the heating circuit                                             |
| 4  | Rotary knob                                                                   |
| 5  | Actuator with integrated potable water temperature control                    |
| 6  | Connection box for the power supply                                           |
| 7  | Volume flow sensor                                                            |
| 8  | Connection for the circulation pipe                                           |
| 9  | Base plate                                                                    |
| 10 | Spacer for water meter                                                        |
| 11 | Ball valve                                                                    |
| 12 | Drain valve in the primary circuit                                            |
| 13 | Spacer for heat meter                                                         |
| 14 | Connection in the primary supply for the temperature sensor of the heat meter |
| 15 | Hot water temperature sensor                                                  |
| 16 | Filter insert in the primary supply                                           |
| 17 | Connection for derivative temperature control set                             |
| 18 | Ceramic disc valve                                                            |
| 19 | Zone valve for heating circuit control                                        |

# Selection

## Item Numbers


### Regudis W-CE

Station including ceramic disc valves.

|  | Performance range    | Heat exchanger                              | Item no. |
|-----------------------------------------------------------------------------------|----------------------|---------------------------------------------|----------|
|                                                                                   | Performance range 1a | Copper brazed                               | 1343929  |
|                                                                                   | Performance range 1  | Copper brazed                               | 1343930  |
|                                                                                   | Performance range 2  | Copper brazed                               | 1343931  |
|                                                                                   | Performance range 1  | Copper brazed with Sealix® protective layer | 1343950  |
|                                                                                   | Performance range 2  | Copper brazed with Sealix® protective layer | 1343951  |

### Regudis W-CE

Station including ceramic disc valves, without cold water outlet and spacer for water meter.

|  | Performance range   | Heat exchanger | Item no. |
|------------------------------------------------------------------------------------|---------------------|----------------|----------|
|                                                                                    | Performance range 1 | Copper brazed  | 1343960  |
|                                                                                    | Performance range 2 | Copper brazed  | 1343961  |

# Accessories and Spare Parts

## Accessories

Selected accessories for the Regudis W-CE station. For a complete overview, see product catalogue.

| Description                               | Item no. |
|-------------------------------------------|----------|
| Potable water circulation module          | 1344555  |
| Derivative temperature control set        | 1344490  |
| Stainless steel spacer                    | 1349052  |
| Accessory set for equipotential bonding   | 1349983  |
| ClimaCon F 210 room thermostat            | 1155021  |
| Aktor T 2P thermal actuator               | 1012452  |
| Surface-mounted thermal insulation bonnet | 1344870  |

## Spare parts


Selected spare parts for the Regudis W-CE station. For a complete overview, see product catalogue.

| Description                                                                     | Item no. |
|---------------------------------------------------------------------------------|----------|
| Actuator with integrated potable water temperature control                      | 1344491  |
| Power supply unit                                                               | 1344496  |
| Volume flow sensor                                                              | 1344693  |
| Filter insert                                                                   | 1344495  |
| Sealing ring for junction G $\frac{3}{4}$                                       | 1344497  |
| Sealing ring for junction G 1                                                   | 1344498  |
| Potable water temperature sensor                                                | 1344494  |
| Heat exchanger copper brazed, performance range 1                               | 1344083  |
| Heat exchanger copper brazed, performance range 2                               | 1344084  |
| Heat exchanger copper brazed with Sealix® protective layer, performance range 1 | 1344093  |
| Heat exchanger copper brazed with Sealix® protective layer, performance range 2 | 1344094  |
| Control valve with integrated differential pressure and volume flow control     | 1344492  |
| Stuffing box screw for control valve                                            | 9010491  |
| Ceramic disc valve                                                              | 1344780  |




# Design Charts


Pressure loss of the primary circuit during heating mode for performance ranges 1a-2



Pressure loss of the potable water circuit for potable water heating for performance ranges (LB) 1a-2




Pressure loss of the primary circuit for potable water heating for performance ranges (LB) 1a-2




# Performance range 1a: Heating of potable water from 10 °C to 45 °C

(Performance data according to SPF test procedure)

## Volume flow of the primary circuit at different flow temperatures




## Return temperature of the primary circuit at different flow temperatures




# Performance range 1a: Heating of potable water from 10 °C to 50 °C

(Performance data according to SPF test procedure)

## Volume flow of the primary circuit at different flow temperatures




## Return temperature of the primary circuit at different flow temperatures




# Performance range 1a: Heating of potable water from 10 °C to 55 °C

(Performance data according to SPF test procedure)

Volume flow of the primary circuit at different flow temperatures




Return temperature of the primary circuit at different flow temperatures




# Performance range 1a: Heating of potable water from 10 °C to 60 °C

(Performance data according to SPF test procedure)

Volume flow of the primary circuit at different flow temperatures




Return temperature of the primary circuit at different flow temperatures




# Performance range 1: Heating of potable water from 10 °C to 45 °C

(Performance data according to SPF test procedure)

Volume flow of the primary circuit at different flow temperatures




Return temperature of the primary circuit at different flow temperatures




# Performance range 1: Heating of potable water from 10 °C to 50 °C

(Performance data according to SPF test procedure)

## Volume flow of the primary circuit at different flow temperatures



## Return temperature of the primary circuit at different flow temperatures







# Performance range 1: Heating of potable water from 10 °C to 55 °C

(Performance data according to SPF test procedure)

Volume flow of the primary circuit at different flow temperatures




Return temperature of the primary circuit at different flow temperatures




# Performance range 1: Heating of potable water from 10 °C to 60 °C

(Performance data according to SPF test procedure)

Volume flow of the primary circuit at different flow temperatures




Return temperature of the primary circuit at different flow temperatures




## Performance range 2: Heating of potable water from 10 °C to 45 °C

(Performance data according to SPF test procedure)

### Volume flow of the primary circuit at different flow temperatures




### Return temperature of the primary circuit at different flow temperatures




## Performance range 2: Heating of potable water from 10 °C to 50 °C

(Performance data according to SPF test procedure)

### Volume flow of the primary circuit at different flow temperatures




### Return temperature of the primary circuit at different flow temperatures




## Performance range 2: Heating of potable water from 10 °C to 55 °C

(Performance data according to SPF test procedure)

### Volume flow of the primary circuit at different flow temperatures




### Return temperature of the primary circuit at different flow temperatures




# Performance range 2: Heating of potable water from 10 °C to 60 °C

(Performance data according to SPF test procedure)

## Volume flow of the primary circuit at different flow temperatures



## Return temperature of the primary circuit at different flow temperatures



Subject to changes • All rights reserved • © 2025 Oventrop GmbH & Co. KG  
EN-06201-13439-DB-V2513 – March 2025