#### **Product Data**



# **Check Valves PN 25**

with FKM or EPDM seal DN 10...50



Backflow preventer made of brass for horizontal and vertical installation. Valve plug spring-loaded. For central heating and cooling systems with closed circuits and industrial plants. Not suitable for use with pulsating flow or within a distance of  $10 \times DN$  downstream of a pump.

Valve plug seal of FKM or EPDM for various applications:


- With FKM seal (item no. 10722..):
   For operation with water or water-glycol mixtures according to VDI 2035 / ÖNORM 5195 (max. 50% glycol content, pH value 6.5...10) as well as non-aggressive, non-hazardous liquids.
   Material resistance: Mineral, heating and hydraulic oils, fuels and air. Not suitable for gaseous fluids group 1 according to Directive 2014/68/EU. The standards and regulations applicable to the use of this media may restrict the temperature range.
- With EPDM seal (item no. 10723..):
   For operation with water (also potable water) or water-glycol mixtures according to VDI 2035 or ÖNORM 5195 (max. 50% glycol content, pH value 6.5...10).

## **Technical Data**

Nominal sizes	DN 1050				
Variants	DN 1020: with internal thread according to EN 10226				
	DN 2550: with internal thread according to ISO 228				
Operating temperature	ltem no. 10722: 0100°C				
	Item no. 10723: -10150°C				
Operating pressure	PN 25				
Medium	Water, water-glycol mixture with a max. glycol content of 50% according to VDI 2035 / ÖNORM 5195				
	Variant with FKM seal also for: Mineral, heating and hydraulic, oils, fuels and air. Not suitable for gaseous fluids group 1 according to Directive 2014/68/EU				
	Variant with EPDM seal also for: Potable water				
Opening pressure	40 mbar				
Kvs values	3.462.1				

## Dimensions and item numbers


DN	Connection d	L [mm]	H [mm]	H1 [mm]	SW [mm]	t [mm]	ltem no. FKM seal	ltem no. EPDM seal
10	Rp ³∕8	62	49	42	21	11.2	1072203	1072303
15	Rp 1/2	65	79	62	25	14.2	1072204	1072304
20	Rp 3/4	75	92	72	31	15.2	1072206	1072306
25	G 1	90	111	87	38	17.7	1072208	1072308
32	G 1 1/4	110	121	96	50	21.4	1072210	1072310
40	G 1 ½	120	135	106	55	21.4	1072212	1072312
50	G 2	150	168	131	67	25.7	1072216	1072316



## **Materials**

Component	10722	10723		
Body	Br	ass		
Bonnet	Br	ass		
Plug seal	FKM	EPDM		
Bonnet seal	FKM	EPDM		

#### Flow chart



# Kvs values

Nominal size	DN 10	DN 15	DN 20	DN 25	DN 32	DN 40	DN 50
Kvs value	3.4	6.0	10.9	17.8	28.2	41.2	62.1

