

We, **Oventrop GmbH & Co. KG**

Paul-Oventrop-Str.1
D-59939 Olsberg

hereby declare at sole responsibility that the following products are designed for
detachable connections with male pipe thread G 3/4 A
according to
DIN EN 16313


Product

**Compression fittings, nipples
and connection pieces "Cofit S"**

Item no.	Dimension	Max. operating pressure p_s	Operating temperature range t_s	CE-marking
150 79 54	14 x 2,0 mm x G 3/4 collar nut	10 bar (PN 10)	0°C up to +95°C	No
150 79 55	16 x 2,0 mm x G 3/4 collar nut			
150 79 59	17 x 2,0 mm x G 3/4 collar nut			
150 79 58	18 x 2,0 mm x G 3/4 collar nut			
150 79 60	20 x 2,0 mm x G 3/4 collar nut			
150 79 74	14 x 2,0 mm x G 3/4 collar nut			
150 79 75	16 x 2,0 mm x G 3/4 collar nut			
150 79 80	20 x 3,0 mm x G 3/4 collar nut			
150 31 61	R 3/8 x G 3/4 male thread			
150 31 62	R 1/2 x G 3/4 male thread			
150 31 64	R 3/4 x G 3/4 male thread			
150 31 51	R 3/8 x G 3/4 male thread			
150 31 52	R 1/2 x G 3/4 male thread			
150 30 53	G 3/8 IG x G 3/4 male thread			
150 30 54	G 3/4 IG x G 3/4 male thread			

Olsberg, 09.02.2015

i. V.



Dr. Foitzik
Technical director

i. A.



Dipl.-Ing. Wilmes
Project manager