

We, **Oventrop GmbH & Co. KG**

Paul-Oventrop-Str.1
D-59939 Olsberg

hereby declare at sole responsibility that the following products are designed for detachable connections with male pipe thread G 3/4 A according to **DIN EN 16313**


Product

Compression fittings, nipples and connection pieces "Cofit S"

| Item no. | Dimension | Max. operating pressure p_s | Operating temperature range t_s | CE-marking |
|-----------|--------------------------------|-------------------------------|-----------------------------------|------------|
| 150 79 54 | 14 x 2,0 mm x G 3/4 collar nut | 10 bar (PN 10) | 0°C up to +95°C | No |
| 150 79 55 | 16 x 2,0 mm x G 3/4 collar nut | | | |
| 150 79 59 | 17 x 2,0 mm x G 3/4 collar nut | | | |
| 150 79 58 | 18 x 2,0 mm x G 3/4 collar nut | | | |
| 150 79 60 | 20 x 2,0 mm x G 3/4 collar nut | | | |
| 150 79 74 | 14 x 2,0 mm x G 3/4 collar nut | | | |
| 150 79 75 | 16 x 2,0 mm x G 3/4 collar nut | | | |
| 150 79 80 | 20 x 3,0 mm x G 3/4 collar nut | | | |
| 150 31 61 | R 3/8 x G 3/4 male thread | | | |
| 150 31 62 | R 1/2 x G 3/4 male thread | | | |
| 150 31 64 | R 3/4 x G 3/4 male thread | | | |
| 150 31 51 | R 3/8 x G 3/4 male thread | | | |
| 150 31 52 | R 1/2 x G 3/4 male thread | | | |
| 150 30 53 | G 3/8 IG x G 3/4 male thread | | | |
| 150 30 54 | G 3/4 IG x G 3/4 male thread | | | |


Olsberg, 09.02.2015

i. V.



Dr. Foitzik
Technical director

i. A.



Dipl.-Ing. Wilmes
Project manager